

Job / Project Name	
Product Model Number	
Quantity	
Date	

APPLICATIONS

Parking lots, building facades, parks, indoor and outdoor applications, and residential and landscaping.

PRODUCT FEATURES

- **Wattages:** 20W, 30W, 50W
- **Color Temperatures:** 45K (standard), 27K, 30K, 40K, 55K, 65K (special order)
- **Voltage Input:** 120-277VAC
- **Beam Angle:** 120 degrees
- **LED Lifespan:** 50,000 hours



IP65

SPECIFICATIONS

PRODUCT #	WATTAGES	DIMENSIONS (WxLxD)	LUMENS (+/-10%)	SUGGESTED HID EQUIV.
ZPW-FL-45K-20W	20W	6.49" x 5.90" x 2.16"	1,800	50-100W
ZPW-FL-45K-30W	30W	6.89" x 6.30" x 2.75"	2,700	100-150W
ZPW-FL-45K-50W	50W	9.25" x 7.87" x 3.74"	4,500	150-200W

NOTE: See website for more information.

PRODUCT BUILDER

ZPW-FL	-		-		=	
Type		Color Temperature		Wattage		Ex: ZPW-FL-45K-30W
		45K (standard)		20W		
		65K		30W		
		55K		50W		
		40K				
		30K				
		27K				