

180° LED CORN PADDLE LAMPS

Angle distribution spreads light side to side from fixture to ground.



Base rotates to give proper light distribution once in socket.



100-150W fan cooled



Lamp Fixture Support Rods - 6.25"
(Trimable in 3/8-inch increments)

RETROFIT EXISTING FIXTURES



APPLICATIONS

- Street lights
- Landscape lighting
- Wall packs
- Shoeboxes
- Enclosed and outdoor fixtures

PRODUCT SPECIFICATIONS

WATTAGES	60W, 80W, 100W, 120W, 150W
COLOR TEMPS	50K (standard), 30K, 40K, 57K (special order)
EFFICACY	155 lm/W
LUMENS	60W- 9,000; 80W- 12,000; 100W- 15,000; 120W- 18,000; 150W- 22,500
INPUT VOLTAGE	120/277V
CRI	>80
BASE TYPE	E26 - Only 60W E39 - All Wattages
OPERATING TEMP	-4° to 104°F
LED LIFESPAN (L70)	50,000 hours
BEAM ANGLE	180°
DIMENSIONS	60W- 3.94" x 9.25" x 2.72" 80W+100W+120W+150W 5.12" x 11.54" x 3.82"
SUGGESTED HID EQUIV.	60W- 175-250W; 80W- 250-400W; 100W- 400W; 120W- 400-500W; 150W- 400-600W
RATED	IP54
LISTED	ETL
WARRANTY	5 year

Comes with Locking Lamp supports standard

NOTE: Approved for suitable use in enclosed fixtures for all. Ballast bypass.



PRODUCT BUILDER

ex: ZL-NS-ARK-E39-80W-50K

TYPE	BASE	WATTAGE	COLOR TEMP
ZL-NS-ARK	-	-	-
	E26 (Only 60W) E39	60W 80W 100W 120W 150W	Standard 50K Special Order 57K 40K 30K