

## PYRAMID LED CORN LAMPS



Sends light to the ground



### RETROFIT EXISTING FIXTURES



### APPLICATIONS

- Warehouse and manufacturing high bays
- Parking garages



### PRODUCT SPECIFICATIONS

WATTAGES	30W, 40W, 60W, 70W, 80W
COLOR TEMPS	50K (standard), 30K, 40K, 60K (special order)
EFFICACY	180 lm/W
LUMENS	30W - 5,400, 40W - 7,200, 60W - 10,080, 70W - 12,600, 80W - 14,400
INPUT VOLTAGE	120/277V 480VAC - Special Order (40W, 60W, 70W, 80W)
CRI	>80
BASE TYPE	E26 - 30W, 40W, 60W E39 - All Wattages E39 using #8 adapter adds no extra length. Ballast bypass.
OPERATING TEMPS	-4 to 104F
LED LIFESPAN (L70)	50,000 hours
DIMENSIONS	E26 - 30W, 40W, 60W 4.17" x 6.69" E39 - 30W, 40W, 60W, 70W 4.17" x 7.09" E39 - 80W 5.20" x 8.39"
SUGGESTED HID EQUIV.	30W - 175-200W, 40W - 200-250W, 60W - 250-350W, 70W - 350-400W, 80W - 400-475W
LISTED	ETL
WARRANTY	5 year

\* Suitable for enclosed fixtures

### PRODUCT BUILDER

ex: ZL-YL-PYR-E26-30-50K

TYPE	BASE	WATTAGE	COLOR TEMP	INPUT VOLTAGE
ZL-YL-PYR	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	E26=Medium E39=Mogul	E26 and E39 30=30W 40=40W* 60=60W* E39 70=70W* 80=80W* *480V Special Order	Standard 50K=5000K Special Order 30K=3000K 40K=4000K 60K=6000K	Blank=120/277V 480VAC (special order)