

UFO-STYLE LED HIGH BAY - High Wattage

Job / Project Name	
Product Model Number	
Quantity	
Date	

APPLICATIONS

Warehouses and manufacturing factories, parking garages, and gymnasiums.

PRODUCT FEATURES

- **Wattages:** 300W, 400W, 500W
- **Color Temperatures:** 27K, 30K, 40K, 50K, 65K
- **Voltage Input:** 100-277VAC, 480VAC optional
- **CRI:** >80Ra
- **Lumens:** 165lm/W
- **Operating Temperature:** -4 to 149°F
- **LED Lifespan:** 100,000 hours
- **Beam Angle:** 60, 90 & 120 degrees
- **Warranty:** 5 years
- **Dimming:** 0-10V optional
- **Lens:** Acrylic



300-500W



MB - Mounting
Bracket Optional.



Hanging loop (standard)
Supports 3/8" threaded rod.



SPECIFICATIONS

PRODUCT #	WATTAGES	DIMENSIONS (WxH)	LUMENS (+/-10%)	SUGGESTED HID EQUIV.	CERT.
ZL-UFO-300W-50K	300W	15.35" x 9.65"	49,500	1,000W	UL
ZL-UFO-400W-50K	400W	15.35" x 9.65"	66,000	1,200W	UL
ZL-UFO-500W-50K	500W	15.35" x 9.65"	82,500	1,500W	UL

NOTE: See website for more information and mounting options.

PRODUCT BUILDER

ZL-UFO	-	Wattage	-	Color Temperature	-	Voltage Input	-	Dimming	=	Ex: ZL-UFO-300W-50K-100-277VAC
Type		300W		65K		100-277VAC		DIM (optional)		
		400W		50K		480VAC				
		500W		40K						
				30K						
				27K						

Specifications and actual product may vary.

Office (800) 679-9243 • sales@zledlighting.com • www.zledlighting.com

OPTIONS (ORDER SEPARATELY)



MB-UFO
(mounting bracket)



SC-UFO
(safety cable)



MS-UFO
(motion sensor)



R-UFO
(reflector)



H-UFO
(hook)