

180° COASTAL FRIENDLY AMBER 585NM LED PADDLE



Lamp Fixture
Support Rods - 6.25"
(Trimable in 3/8-inch
increments)



The 180-degree beam angle paddle design allows for focused light distribution in one direction, making it ideal for applications where directed lighting is necessary. This can enhance visibility and reduce wasted light, making them more efficient than traditional LED corn lamps, which often emit light in all directions.

Commonly used in street lights, wall packs and area lights. The 585NM LED chips are turtle friendly based on the FWC Specs for Sea Turtle Lighting.

APPLICATIONS

- Area Lights
- Street lights
- Landscape lighting
- Wall packs
- Rated for Enclosed fixtures

PRODUCT FEATURES

WATTAGES	40W, 60W, 80W, 100W, 120W, 150W
COLOR TEMPS	Amber 585NM
EFFICACY	31 lm/W
INPUT VOLTAGE	100-277VAC
CRI	Ra=26.0
BASE TYPE	E26 - 40W, 60W; E39 - all Wattages
WAVELENGTH	585 nanometers
LED LIFESPAN	50,000 hours
BEAM ANGLE	180 degrees
RATED	IP54
LISTED	ETL
WARRANTY	5 years

Bases are 340° Rotatable

SPECIFICATIONS

PRODUCT #	WATTAGES	DIMENSIONS (WxL)	BASE TYPE
ZL-NS-ARK-E26-40W-585NM-AMBER	40W	3.94" x 9.25" x 2.72"	E26
ZL-NS-ARK-E39-40W-585NM-AMBER	40W	3.94" x 9.25" x 2.72"	E39
ZL-NS-ARK-E26-60W-585NM-AMBER	60W	3.94" x 9.25" x 2.72"	E26
ZL-NS-ARK-E39-60W-585NM-AMBER	60W	3.94" x 9.25" x 2.72"	E39
ZL-NS-ARK-E39-80W-585NM-AMBER	80W	5.12" x 11.54" x 3.82"	E39
ZL-NS-ARK-E39-100W-585NM-AMBER	100W	5.12" x 11.54" x 3.82"	E39
ZL-NS-ARK-E39-120W-585NM-AMBER	120W	5.12" x 11.54" x 3.82"	E39
ZL-NS-ARK-E39-150W-585NM-AMBER	150W	5.12" x 11.54" x 3.82"	E39

NOTE: Approved for suitable use in enclosed fixtures for all. Ballast bypass.



Lighting pollution is a serious threat to many types of wildlife. Each year, artificial light causes disruption of behavior, injury, and death to thousands of sea turtles.