

LED FLOOD LIGHT



IP65

APPLICATIONS

- Parking Lots
- Tunnels
- Parks
- Walkways
- Sports courts
- Billboard lighting

PRODUCT SPECIFICATIONS

WATTAGES	100W, 150W, 200W, 300W
COLOR TEMPS	50K (standard), 30K, 40K (special order)
EFFICACY	110 lm/W
LUMENS	100W- 11,000; 150W- 16,500; 200W- 22,000; 300W- 42,000
INPUT VOLTAGE	100-277VAC, 200-480VAC
CRI	>80+
BEAM ANGLE	120°
LED LIFESPAN (L70)	50,000 hours
DIMENSIONS (WxLxD)	100W- 16.33" x 11.61" x 2.39" 150W- 17.71" x 13" X 2.36" 200W- 19.09" x 14.17" x 2.36" 300W- 22.24" x 17.04" x 2.56"
SUGGESTED HID EQUIV.	100W- 200-250W; 150W- 300-400W; 200W- 400-450W; 300W- 500-750W
RATED	IP65
LISTED	ETL
WARRANTY	5 year
PART NUMBERS	ZL-R-FLC-50K-100W
	ZL-R-FLC-50K-150W
	ZL-R-FLC-50K-200W
	ZL-R-FLC-50K-300W