

4 FT LED WRAPAROUND LED LIGHT FIXTURE WATTAGE AND CCT SELECTABLE - NB SERIES



APPLICATIONS

- Schools
- Warehouses
- Offices
- Kitchens
- Garages
- Hallways


PRODUCT SPECIFICATIONS

WATTAGES	40/35/30W selectable
COLOR TEMPS	35/40/50K selectable
EFFICACY	130 lm/W
LUMENS	40W- 5,200; 35W- 4,550; 30W- 3,900
INPUT VOLTAGE	120/277V
OPERATING TEMP	4°F to 122° F
LED LIFESPAN (L70)	50,000 hours
DIMMING	0-10V
SURGE SUPPRESSION	2.5KV
MOUNTING	Surface and Pendant
DIMENSIONS (LxWxH)	47.7" x 2.8" x 7.1"
MOTION SENSOR	Optional
EMERGENCY BATTERY	Optional
RATED	IP20
LISTED	UL
WARRANTY	5 year

PIR SENSOR WITH 90 DEGREE ARM



Part Number:
ZL-MS-SENSOR-HB-ARM-ANT-6-4T
Optional Part Builder Part Number: MS



Part Number:
ZL-REMOTE-RC-100
(Sold Separately)



PART NUMBER

ZL-4FT-WRAP-CCT-WS-NB

ZL-4FT-WRAP-CCT-WS-NB-MS

ZL-4FT-WRAP-CCT-WS-NB-MS-EM

ACCESSORY



Suspension Kit - V Hook

- For suspending the strip light
- Material: stainless steel

SPECIFICATIONS

Power Supply	12V-24VDC, <30mA
Dim Control Output	0-10V, max. 25mA sinking current
Mounting Height	Max 40ft. (12m)
Detection Radius	20%/50%/75%/100%(1-8m)
Operating Temperature	-4°F-140°F (-20°C-60°C)
IP Rating	IP65

WARNING

NOTE: Warm up time is 40 seconds. After the sensor connects input power first time, the light will keep on 40 seconds, then go to dimming to work normally.
NOTE: Factory Default Setting: 100% sensitivity, Hold on time: 5min, Daylight sensor is-O. Dimming level: 30%, Dimming time: 60 min.
NOTE: Any setting changed by remote control, the led light that sensor connect will on/off as confirm.