

IP64 MINI & SUPER MINI CORN LAMPS - HIGH LUMEN



RETROFIT EXISTING FIXTURES



APPLICATIONS

- Post tops
- Bollards
- Commercial and residential recessed cans
- Institutional and educational facilities
- Tall and wall packs and floods



PRODUCT SPECIFICATIONS

WATTAGES	15W, 25W
COLOR TEMPS	22K, 30K, 40K, 50K
EFFICACY	160 lm/W 190 lm/W
LUMENS	Original- 15W- 2,400; 25W- 4,000 High Lumen- 15W- 2,800; 25W- 4,750
INPUT VOLTAGE	120/277V
CRI	>80
BASE TYPE	E26 medium, E39 mogul E39 supported with Adapter-8
OPERATING TEMP	-20° - 50°C; 4° - 122°F
LED LIFESPAN	50,000 hours
DIMENSIONS	15W- 2.52" x 5.91" 25W- 2.52" x 6.30"
SUGGESTED HID EQUIV	15W- 50-75W 25W- 100-175W
RATED	IP64
LISTED	ETL
WARRANTY	5 year

NOTE: Approved for suitable use in enclosed fixtures for all. Medium base (E26) can be converted to Mogul base (E39) without adding any length by using "Adapter-B". Replaces HID Mini 75-150W. Ballast bypass.
Example: C-E26-15-50K-IP64-MINI

PART NUMBERS – 160 lm/W

MINI	C-E26-15-22K-IP64-MINI
	C-E26-15-40K-IP64-MINI
SUPER MINI	C-E26-25-22K-IP64-S-MINI
	C-E26-25-30K-IP64-S-MINI
	C-E39-25-22K-IP64-S-MINI
	C-E39-25-30K-IP64-S-MINI
	C-E39-25-40K-IP64-S-MINI
	C-E39-25-50K-IP64-S-MINI

PART NUMBERS – 190 lm/W

MINI HIGH LUMEN	C-E26-15-30K-IP64-MINI-HL
	C-E26-15-50K-IP64-MINI-HL
SUPER MINI HIGH LUMEN	C-E26-25-40K-IP64-S-MINI-HL
	C-E26-25-50K-IP64-S-MINI-HL