

LINE VOLTAGE FLEXIBLE LED STRIP LIGHTS



Whole rolls available



RGB 5050



Extra Bright 5050



Standard 3528



APPLICATIONS

- Kitchens
- Showrooms
- Outdoor applications
- Bars
- Cove lighting
- Custom projects
- Walls
- Under bars
- Walkways
- Tent lighting

Suitable for damp and wet locations, including outdoor use.

PRODUCT FEATURES

WATTAGES	1.5W, 3.03W
COLOR TEMPS	30K, 40K, 65K, Red, Blue, RGB
INPUT VOLTAGE	120VAC
DIMMING	120V (Standard)
CUTTABLE	Approx. every 19"
LED LIFESPAN (L70)	50,000 hours
DIMENSIONS (WxH)	Standard- 3/8" x 1/4" Extra Bright+RGB- 1/2" x 5/16"
MAX LENGTHS	Standard- 328ft. Extra Bright+RGB- 164ft.
RATED	IP65
LISTED	ETL
WARRANTY	2 year

Subject to National Electric Code (NEC) and local code requirements.

SPECIFICATIONS

	PRODUCT #	PINS	WATTAGES PER FOOT	LED TYPE & SIZE	LUMENS (+/-10%)
	LF-30K-3528	2	1.5W	Standard 3528	73.15 per foot
	LF-65K-3528	2	1.5W	Standard 3528	73.15 per foot
COLORS	LF-RED-3528	2	1.5W	Standard 3528	73.15 per foot
EXTRA BRIGHT	LF-EB-30K-5050	2	3.03W	Extra Bright 5050	220 per foot
	LF-EB-40K-5050	2	3.03W	Extra Bright 5050	220 per foot
	LF-EB-RED-5050	2	3.03W	Extra Bright 5050	223 per foot
	LF-EB-BLUE-5050	2	3.03W	Extra Bright 5050	225 per foot
	LF-RGB-5050	4	3.03W	5050 SMD	229 per foot

NOTE: Standard order usually entails: a length of line flex, power supply cord or RGB controller, 2 or 4-pin connector, end cap and mounting clips. Mounting hardware available. Cuttable every 19". Cut charge may apply. Use heat shrink and silicone on connection points and end caps.

SINGLE COLOR/RGB LINEFLEX ACCESSORIES



Power Supply Cord



Pin Connectors



Connectors




End Caps



Couplings



Mounting Clips



Mounting Channel LF-MOUNT-UNIV-4FT

PRODUCT #	DESCRIPTION
LF-REMOTE-CONTROLLER-RGB	RGB controller & remote, 1,500W MAX, 120VAC
LF-PS-3528-ETL	3528 Power supply cord 19"
LF-PS-5050-ETL	5050 Power supply cord 19" (extra bright)
LF-PS-10-3528-ETL	3528 Power Supply Cord 10' (white)
LF-PS-10-5050-ETL	5050 Power Supply Cord 10' (white)
LF-PS-10-5050-ETL-Black	5050 Power Supply Cord 10' (black)
LF-PS-15-5050-ETL-Black	5050 Power Supply Cord 15' (black)
LF-2PIN-CONN-3528	3528 Connecting metal pins 2-pin
LF-2PIN-CONN-5050	5050 Connecting metal pins 2-pin (extra bright)
LF-4PIN-CONN-RGB	RGB Connecting metal pins 4-pin
LF-EB-90-CONN	90 Degree connector, comes with two (LF-2PIN-CONN-5050)
LF-EB-T-CONN	T Connector (3-way), comes with three (LF-2PIN-CONN-5050)
LF-EB-Short-Jump	Short jumper 6" (flexible), comes with two (LF-2PIN-CONN-5050)
ENDCAP-3528	3528 End cap
ENDCAP-5050	5050 End cap (extra bright)
ENDCAP-5050-RGB	5050 End cap (RGB)
LF-CONN-3528	3528 Connector
LF-CONN-5050	5050 Connector (extra bright)
LF-RGB-CONN	RGB Connector
MTCLIP-3528	1" x .38" x .31" 3528 Mounting clip
MTCLIP-5050	1.25" x .50" x .38" 5050 Mounting clip
MTCLIP-5050-RGB	1.25" x .50" x .38" 5050 Mounting clip (RGB)
LF-MOUNT-UNIV-4FT	48" Aluminum mounting channel Standard 3528, Extra Bright 5050, RGB

48" length, 11/16" width; 5/16 height